



SAFETY DATA SHEET

PRETON R303 PX2

Page: 1

Compilation date: 10/10/2014

Revision date: 05/02/2016

Revision No: 4

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: PRETON R303 PX2

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Metal forming fluid

1.3. Details of the supplier of the safety data sheet

Company name: ROCOL

ROCOL House

Swillington

Leeds

West Yorkshire

LS26 8BS

ENGLAND

Tel: +44 (0) 113 232 2700

Fax: +44 (0) 113 232 2740

Email: customer-service@rocol.com

1.4. Emergency telephone number

Emergency tel: +44 (0) 113 232 2600

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Asp. Tox. 1: H304; Aquatic Chronic 3: H412; -: EUH066

Most important adverse effects: Repeated exposure may cause skin dryness or cracking. May be fatal if swallowed and enters airways. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: EUH066: Repeated exposure may cause skin dryness or cracking.

H304: May be fatal if swallowed and enters airways.

H412: Harmful to aquatic life with long lasting effects.

Hazard pictograms: GHS08: Health hazard



Signal words: Danger

[cont...]

SAFETY DATA SHEET

PRETON R303 PX2

Page: 2

Precautionary statements: P273: Avoid release to the environment.
P301+310: IF SWALLOWED: Immediately call a.
P331: Do NOT induce vomiting.
P405: Store locked up.
P501: Dispose of contents/container to local/national regulations.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

ODOURLESS KEROSENE - REACH registered number(s): 01-2119456620-43-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
926-141-6	64742-47-8	-	Asp. Tox. 1: H304; -: EUH066	50-70%

MINERAL OIL (NOTE L <3% DMSO EXTRACTABLE COMPONENTS)

265-155-0	64742-52-5	Substance with a Community workplace exposure limit.	-	10-30%
-----------	------------	--	---	--------

ALIPHATIC ALCOHOL - REACH registered number(s): 01-2119486890-26-0001, 01-2119485848-16-0001, 01-2119485848-16-0003

278-306-0	75782-86-4	-	Aquatic Acute 1: H400; Aquatic Chronic 2: H411	1-10%
-----------	------------	---	--	-------

CALCINATE C300R

-	-	-	Eye Irrit. 2: H319	1-10%
---	---	---	--------------------	-------

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: There may be coughing and a sore throat.

4.3. Indication of any immediate medical attention and special treatment needed

[cont...]

SAFETY DATA SHEET

PRETON R303 PX2

Page: 3

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Use water spray to cool containers. Suitable extinguishing media for the surrounding fire should be used.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

[cont...]

SAFETY DATA SHEET

PRETON R303 PX2

Page: 4

ODOURLESS KEROSENE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1200	-	-	-

MINERAL OIL (NOTE L <3% DMSO EXTRACTABLE COMPONENTS)

UK	5mg/m3	10mg/m3	-	-
----	--------	---------	---	---

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Respiratory protection: Respiratory protection not normally required.

Hand protection: Protective gloves.

Eye protection: Safety glasses with side-shields.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Brown

Odour: Characteristic odour

Evaporation rate: Negligible

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Insoluble

Viscosity: Non-viscous

Flash point°C: 70

Autoflammability°C: > 200

Relative density: 0.84

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid: Heat.

[cont...]

SAFETY DATA SHEET

PRETON R303 PX2

Page: 5

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong reducing agents.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes of carbon dioxide / carbon monoxide.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

ODOURLESS KEROSENE

DERMAL	RBT	LD50	>5000	mg/kg
ORAL	RBT	LD50	>5000	mg/kg
VAPOURS	RAT	4H LC50	>5000	mg/l

MINERAL OIL (NOTE L <3% DMSO EXTRACTABLE COMPONENTS)

DERMAL	RBT	LD50	>5000	mg/kg
ORAL	RAT	LD50	>5000	mg/kg

ALIPHATIC ALCOHOL

DERMAL	RAT	LD50	>5000	mg/kg
ORAL	RAT	LD50	>5000	mg/kg

CALCINATE C300R

ORAL	RAT	LD50	>20000	mg/kg
------	-----	------	--------	-------

Relevant hazards for product:

Hazard	Route	Basis
Aspiration hazard	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: There may be coughing and a sore throat.

Section 12: Ecological information

12.1. Toxicity

[cont...]

SAFETY DATA SHEET

PRETON R303 PX2

Page: 6

Hazardous ingredients:

ODOURLESS KEROSENE

ALGAE	72H IC50	20	mg/l
Daphnia magna	48H EC50	>250	mg/l
FISH	96H LC50	>1000	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	>1000	mg/l

ALIPHATIC ALCOHOL

FISH	-	<1	mg/l
------	---	----	------

CALCINATE C300R

FISH	96H LC50	>10000	mg/l
------	----------	--------	------

12.2. Persistence and degradability

Persistence and degradability: Only slightly biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Non-volatile. Absorbed only slowly into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

[cont...]

SAFETY DATA SHEET

PRETON R303 PX2

Page: 7

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

Compiled in accordance with REACH.

Phrases used in s.2 and s.3: EUH066: Repeated exposure may cause skin dryness or cracking.

H304: May be fatal if swallowed and enters airways.

H319: Causes serious eye irritation.

H400: Very toxic to aquatic life.

H411: Toxic to aquatic life with long lasting effects.

H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

