

# DYKEM®

## CROSS CHECK™ PLUS

### AVIATION GRADE TORQUE SEAL®



# SEAL OF APPROVAL

**BRINGING  
MORE  
VALUE TO  
AIRCRAFT  
ASSEMBLY  
AND  
MAINTENANCE**

The improved formulation and durability of Cross Check™ Plus means you can trust it to **EXPEDITE QUALITY AND SAFETY CHECKS** for both aircraft assembly and maintenance/repair processes. The highly visible formula meets all requirements for Boeing Specification BMS8-45H, Type I/III. Working conditions require a **QUICK-DRY** product to keep up with demands of the assembly process, and resistance to Skydrol® PE-5 for **LONG-TERM DURABILITY** in the operation of the aircraft. That's exactly what Cross Check™ Plus delivers with unsurpassed resistance to hydraulic fluids while being dry-to-the-touch in less than a minute! **FULL CURE TIME IS REALIZED IN JUST 24 HOURS.** It's the only torque sealant on the market that can make those claims.

- Aluminum tube and nozzle allow for 2-year shelf life - **LESS WASTED PRODUCT**
- Approved product replacement for Organic F-925 Torque Sealant

**CONTACT YOUR DISTRIBUTOR TODAY OR VISIT [DYKEM.COM](http://DYKEM.COM) FOR DETAILS.**



### Only torque sealant that offers...

- Skydrol®-Resistance\*
- Easy to detect fluorescent colors
- Dry-to-the-touch in less than 60 seconds
- Full cure time: 24 hours
- 2-Year shelf life - best in industry

**...in a single formulation**



### DYKEM® CROSS CHECK™ PLUS

**AVIATION GRADE TORQUE SEAL®** has once again raised the bar of excellence by developing a Skydrol®-Resistant Torque Seal® that delivers a maximum full cure time of 24 hours. The new formulation is the only torque sealant product that meets the rigorous Boeing specification for touch-dry time, full cure time and durability when exposed to Skydrol® and other harsh solvents. It provides you with the peace of mind knowing your critical fasteners remain properly torqued.

- Visually detect loose nuts and bolts
- Use on all critical fittings and locknuts during OEM and maintenance procedures
- Perfect for use on landing gear, rotor assemblies, gearboxes, Palnut® and more
- For use in any aircraft environment with possible fluid exposure

### Technical Detail:

- \*Passes RVCA DO-160G Fluids Susceptibility Test (Section 11, Spray) for Skydrol® PE-5 hydraulic fluid
- Meets requirements for Boeing Specification BMS8-45H, Type I/III
- Approved product replacement for Organic F-925 Torque Sealant

### AVAILABLE PRODUCTS

Part No.	Color	Container	Case Pack	Case Wt.
83417	Yellow	1 oz Tube	24	2 lbs.
83418	Lt. Blue	1 oz Tube	24	2 lbs.
83420	Pink	1 oz Tube	24	2 lbs.

## PLACE YOUR ORDER TODAY!

ROCOL®



Performance you can trust

CONTACT ROCOL® SOUTH AFRICA TODAY!

☎ . 011 462 1730 ✉ . Sales@rocol.co.za 🌐 . www.rocol.co.za